

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

1-12. (canceled)

13. (currently amended) ~~Clamping~~ A clamping device (1) for telescoping tubes (3, 5), ~~especially of poles or staffs used in sports,~~ comprising:

~~with~~

a threaded part (7) comprising a threaded rod (11) configured for attachment to an inner tube (3) of a set of telescoping tubes (3, 5),

the threaded rod (11) comprising two threaded sections (13, 15),

the two threaded sections having opposing threads,

a radially expandable clamping part (21) which is a hollow cylinder and which has a continuous lengthwise slot (25),

two conical expansion bodies (17, 19) located at respective ones of ~~being assigned to the~~ two opposite ends of the clamping part (21), wherein,

~~characterized in that~~

the two expansion bodies (17, 19) are adjustable ~~can be~~ moved relative to the clamping part (21),

~~that~~ the expansion bodies (17, 19) are each threaded
~~serewed~~ onto a different one of the threaded sections (13, 15) of
the threaded rod (11) ~~with opposing threads~~, and

in use, the expansion bodies (17, 19) engage an
interior of an outer tube (5) of the set of telescoping tubes (3,
5), turning the inner tube (3) relative to the outer tube (5)
causes the expansion bodies (17, 19) to move along the respective
one of the different threaded sections to each approach the other
to widen the clamping part (21) radially, over a length of the
clamping part (21)

~~that a threaded part (7) which has a threaded rod (11)~~
~~is attached to the inner tube (3) of the telescoping tubes (3, 5).~~

14. (currently amended) The clamping ~~Clamping~~ device as
claimed in claim 13, wherein the threaded section (13) which, in
use, is adjacent to the inner tube (3) has a greater diameter than
the threaded section (15) which, in use, is remote from the inner
tube (3).

15. (currently amended) The clamping ~~Clamping~~ device as
claimed in claim 13, wherein the hollow cylinder which forms the
clamping part (21) has recesses (23) which proceed from its two
ends.

16. (canceled)

17. (currently amended) The clamping ~~Clamping~~ device as claimed in claim 15, wherein the recesses (23) are offset by 90 degrees to one another on the ends of the hollow cylinder.

18. (currently amended) The clamping ~~Clamping~~ device as claimed in claim 13, wherein the expansion bodies (17, 19) with their ends of smaller diameter engage the clamping part (21).

19. (currently amended) The clamping ~~Clamping~~ device as claimed in claim 13, wherein the expansion bodies (17, 19) on their ends with the greater diameter are made to increase friction relative to the material of the outer tube (5).

20. (currently amended) The clamping ~~Clamping~~ device as claimed in claim 14, wherein the hollow cylinder which forms the clamping part (21) has recesses (23) which proceed from its two ends.

21. (currently amended) The clamping ~~Clamping~~ device as claimed in claim 16, wherein the recesses (23) are offset by 90 degrees to one another on the ends of the hollow cylinder.

22. (new) The combination of the clamping device of claim 13 and the set of telescoping tubes (3, 5) connected to the clamping device.

23. (new) A clamping device, comprising:

a threaded part (7) configured to be inserted into an interior of a tube (3) of a first interior diameter;

a threaded rod (11) projecting from the threaded part (7), and with two threaded sections (13, 15) having opposing threads,

the thread of a first of the two threaded sections (13) having a larger diameter than the opposing threaded thread of a second of the two threaded sections (15);

two conical expansion bodies (17, 19) having internal threads respectively corresponding to the threads of two threaded sections (13, 15),

one expansion body (17, 19) threaded onto each of the two threaded sections;

a radially expandable clamping part (21) located between the two expansion bodies (17, 19) and comprising a cylinder tube with a lengthwise slot (25),

the two expansion bodies (17, 19) having smaller diameter ends engaged with the clamping part (21),

the clamping part (21) being radially expandable under action of the two expansion bodies (17, 19) being brought together,

wherein, greater diameter ends of the two expansion bodies (17, 19) are each dimensioned to frictional engage an inner surface of another tube (5) having a second interior diameter greater than the first interior diameter.

24. (new) The combination of the clamping device of claim 23 and the tube (3) and the another tube (5), wherein, the threaded part (7) is inserted into the tube (3), and

the two expansion bodies engage the interior of an another tube (5),

moving the tube (3) relative to the another tube (5) causing each of the two expansion bodies (17, 19) to move on the respective threaded sections (13, 15) to approach one another and to widen the clamping part 21 radially.

25. (new) A clamping device in combination with two poles, comprising:

a clamping device (1) within two tubes (3, 5),

the clamping device comprising

a threaded rod (11) with two oppositely threaded sections (13, 15),

the threaded rod having a first end engaged with a first of the two tubes,

two expansion bodies (17, 19) each threaded onto a respective one of the two oppositely threaded sections (13, 15),

the two expansion bodies each engaged with a second of the two tubes,

a slotted, cylindrical clamping part (21), located around the threaded rod and between each of the two expansion bodies (17, 19),

wherein, by relative turning of the two tubes (3, 5) the two expansion bodies (17, 19) each penetrate into the clamping part (21) from two ends of the clamping part (21) to radially widen the clamping part over an entire length of the clamping part.

26. (new) A clamping device in combination with two poles of claim 25, wherein, a thread of a first of the two threaded sections (13) has a larger diameter than a an oppositely threaded thread of a second of the two threaded sections (15).